


MB1138

Stretch Corner Armor with Tail Light System - Wrangler JK

Compatible with (2007-2018 Jeep JK)




ASSEMBLY INSTRUCTIONS

MB1138


CONTENTS

MB1138


DRIVER



MB1138-W01
QTY 1




U022-01
QTY 1




U024-A-01
QTY 1


PASSENGER




MB1138-W02
QTY 1




U024-A-02
QTY 1




U022-02
QTY 1




1/4-20 x 1" FHS-SS
QTY 45




1/4-20 x 1/2" BHS-SS
QTY 12




1/4-20 x 3/4" BHS-SS
QTY 10



1/4"-20 Riv Nut YZ
QTY 37




1/4" Flat Washer G8 YZ
QTY 12



#10-24 x 3/4" BHS-SS
QTY 1



#10-24 Nylock Nut SZ
QTY 1




1/4"-20 Nylock Nut G8 YZ
QTY 12

MB1138-T


CONTENTS

MB1138-T (For Fold Down Tailgate)


DRIVER



MB1138-W01
QTY 1




U022-01
QTY 1




U024-A-01
QTY 1


PASSENGER




MB1138-T-W02
QTY 1




U024-A-02
QTY 1




U022-02
QTY 1




1/4-20 x 1" FHS-SS
QTY 45




1/4-20 x 1/2" BHS-SS
QTY 12




1/4" Flat Washer G8 YZ
QTY 12



1/4-20 x 3/4" BHS-SS
QTY 10



1/4"-20 Riv Nut YZ
QTY 37



1/4"-20 Nylock Nut G8 YZ
QTY 12



Preparation and Installation Guide

Compatibility:

This product is designed for 2007-2018 Jeep Wrangler JK 2-door models with a stretched wheelbase.

MB1138 fits vehicles using the factory hinged tailgate.

MB1138-T fits vehicles using the Motobilt MB1184 drop down tailgate.

This armor is intended for stretched wheelbase applications in the 8" to 11" range, depending on tire size. Motobilt recommends approximately a 10" stretch for 42" tires.

Important: Installation of this product requires significant body cutting, modification, and fitting. This is not a minor trim-to-fit installation. Review the full preparation, cutting, and installation procedures before beginning.

1. Rivnuts: This kit requires the use of rivnuts. A 25/64" drill bit will be required for installation.

2. Anti-Seize: The use of anti-seize on hardware is highly recommended.

3. Tail Lights: This kit includes a rear light assembly. The main tail light is pre-wired and ready to plug into the factory JK tail light connector.

4. Baja Designs S1: The rear light assembly also includes a Baja Designs S1 light. This light is not pre-wired into the vehicle and must be wired by the installer to the desired switch or circuit.


5. Stock Tailgate Jeeps: You will need to remove the factory tail gate stop if it is still in the jeep. This will require removing part of the interior which is now shown in the instructions.

Pro Tip: Use STEEL-IT paint in areas that may require touch-up after fitting or modification.

Note: Motobilt, Inc. products are intended for OFF-ROAD USE ONLY. See full legal disclaimer at the end of these instructions.

MB1138


AFTER ENSURE PROPER ALIGNMENTS WITH BODY LINES AND FENDER EDGES MARK ALL THE COUNTERSINK MOUNTING HOLES AND DRILL UP TO 25/64" SO THAT 1/4" RIVNUTS CAN BE INSTALLED. (MARK THE CORNER FOR THE CUTTING THE CORNER PROFILE)



1/4" HOLE FOR THROUGH BOLTS


MB1138

CUT THE REAR CORNER AS LISTED BELOW SO THERE IS ENOUGH CLEARANCE FOR THE LIGHT HOUSING.



MB1138

CUT THE REAR CORNER AS LISTED BELOW SO THERE IS ENOUGH CLEARANCE FOR THE LIGHT HOUSING.




MB1138

AFTER REMOVING THE INTERIOR OF THE REAR PASSENGER CORNER REMOVE THE 4 SHOWN BOLTS ALLOWING THE DOOR STOP TO BE REMOVED.

Factory Fasteners


MB1138



AFTER INSTALLING THE NUT AND BOLT REMOUNT AND SECURE THE DOOR STOP.

MB1138

THE BELOW THE LINE SHOWS WHAT THE REAR CORNER SHOULD LOOK LIKE AFTER CUTTING THE CORNER.



MB1138

INSTALL ALL THE RIVNUTS IN THE DRILLED HOLES

1/4"-20 Riv Nut YZ

MB1138

**ATTACH AND SECURE THE LIGHT HOUSING AND
RING FOR THE CORRESPONDING CORNER.**

(DO NOT OVER TORQUE THE BOLTS SCREWING IN THE THE LIGHT HOUSING.)

**JUST START ALL THE BOLTS TO ALLOW
FOR MISALIGNMENT OF THE TAILLIGHT
HOUSING AND TAILLIGHT RING.**


U022-01
(U022-02 for Passenger Side)

U024-01
(U024-02 for Passenger Side)

1/4-20 x 3/4" BHS-SS
1/4-20 x 1/2" BHS-SS

MB1138

SECURE THE CORNER ARMOR TO THE JEEP USING THE PROVIDED FASTENERS.
CONNECT THE LIGHT PLUG WHILE FITTING THE CORNER.



1/4" Flat Washer G8 YZ

1/4"-20 Nylock Nut G8 YZ

1/4-20 x 1" FHS-SS

LEGAL DISCLAIMER

Motobilt, Inc. products are designed and manufactured primarily for **OFF-ROAD USE ONLY**. They are not certified or approved for street or highway use and may not comply with vehicle safety standards or regulations. Vehicle modifications, including the installation of Motobilt, Inc. products, may alter the handling, performance, and durability of a vehicle.

By purchasing, installing, or using any Motobilt, Inc. product, the purchaser and installer expressly acknowledge and agree to the following terms:

1. ASSUMPTION OF RISK

The purchaser and installer understand and accept that the installation and use of aftermarket products involve inherent risks, including but not limited to vehicle damage, property damage, serious injury, or death. All such risks are voluntarily assumed.

2. NO WARRANTY OF SAFETY

Motobilt, Inc. makes no representations, warranties, or guarantees, express or implied, regarding the safety, performance, or structural integrity of its products. Motobilt, Inc. products are not intended to prevent injury or death in the event of an accident, rollover, or collision.

3. INSTALLATION RESPONSIBILITY

Some Motobilt products require advanced fabrication, cutting, or welding skills. Others may require specialized tools or mechanical knowledge. Motobilt, Inc. is not responsible for improper installation, modification, or misuse of its products. Professional installation by a qualified individual is strongly recommended.

4. COMPLIANCE WITH LAWS AND REGULATIONS

The purchaser and installer are solely responsible for ensuring that the vehicle and installed products comply with all applicable local, state, and federal laws and safety regulations. Vehicle modifications may void factory warranties and may render the vehicle illegal for use on public roads.

5. MAINTENANCE AND INSPECTION

All products should be inspected regularly for signs of wear, fatigue, or damage. Continued use of damaged or improperly installed equipment increases the risk of failure and potential injury. The responsibility for inspection and maintenance rests solely with the owner and operator.

6. WARRANTY DISCLAIMER

Unless expressly stated in a written limited warranty issued by Motobilt, Inc. for a specific product, all Motobilt, Inc. products are sold "as is" and without express warranties of any kind. If a written limited warranty applies, its terms are exclusive and govern the extent of Motobilt, Inc. obligations.

To the fullest extent permitted by law, Motobilt, Inc. expressly disclaims all implied warranties, including but not limited to implied warranties of merchantability, fitness for a particular purpose, and non-infringement. No oral or written statement by Motobilt, Inc., its employees, dealers, or representatives shall constitute or create any warranty, obligation, or liability beyond what is contained in official written documentation issued by Motobilt, Inc.

7. LIMITATION OF LIABILITY

To the fullest extent permitted by law, Motobilt, Inc. disclaims all liability for any direct, indirect, incidental, consequential, or punitive damages arising out of the purchase, installation, or use of its products. This includes, but is not limited to, claims for property damage, personal injury, loss of use, or loss of income.

8. USER ACKNOWLEDGMENT

By purchasing, installing, or using Motobilt, Inc. products, the purchaser and installer acknowledge that they have read, understood, and accepted the terms of this disclaimer and voluntarily assume all associated risks.